



## M 1500 CSF

M 1500 CSH - Roll-in Refrigerator - Remote

Equipped with: Right hand hinged reversible door with positive handle and lock

Roll-in cabinets are designed for temporary refrigerated storage within a production line, for example between blast chillers and refrigerated coldrooms. By utilising roll-in cabinets the refrigeration process is unbroken, ensuring time spent on manual handling and re-loading is kept to a minimum.

Roll-in cabinets are available as refrigerator or freezer, the former with two optional temperature ranges to choose from.

The refrigerators can be supplied with or without a floor and with isolated or glass doors. The freezers are available with isolated door and floor.

The cabinets are available with either an integrated refrigeration system or supplied for connection to a remote refrigeration system.

## TECHNICAL INFORMATION

Varenummer	861500123
Category	Roll-in/through
Type	Roll-in refrigerator
Line	With solid door
Series	GRAM PROCESS
Equipped with	Right hand hinged reversible door with positive handle and lock
Temperature range	-5/+12 °C
Volume, net	1273 ltr./ 45.1 cu.ft.
Volume, gross	1422 ltr./ 50.4 cu.ft.
Exterior/Interior	Stainless/Stainless
Internal, W x D x H	720 x 895 x 1900 mm
External, W x D x H	880 x 1088 x 2338 mm
Weight, packed	160 kg
Insulation	60 mm (cyclopentane)
Refrigerant / GWP	R 134 a/0.34 kg/CO2e 486.20 kg/1430
Ref.capacity at -10°	700 Watt
Connection	230 V, 50 Hz
Connection load	108 Watt

