



## **MB-CHW Assembly**









	REV	DESC	CRIPTION	DATE
	1			
	2			
	3			
	4			
j	5			

PARRY
<b>Built</b> for purpose

PRODUCT:		DRAWN:	DominicW	U
PART NAME: FB-CHW Assembly	CONFIG: N/A	REVISION:	1	Ti A
DWG LOCATION: I:\1 PRODUCT RANGE\FLEXI-BAR\Corner Unit\CHW\		CREATION DA	TE: 14/09/2015	P B B
COPYRIGHT (C) PARRY CATERING FQUIPMENT (MIDLANDS) LTD		LAST UPDATED	: 01/03/2023	ti

Please allow the following for stainless steel bends in a 10mm V:
Steel Push Through Value
0.8MM S/S = 0,92MM
0.9MM S/S = 0,92MM
1.2MM S/S = 1,27MM
1.2MM S/S = 1,27MM
2.MM S/S = 1,45MM
2.MM S/S = 1,45MM
7.MM S/S = 1,45MM
8.MM S/S = 1,45MM
9.MM S/ Unless otherwise specified dimensions are in millimeters. Tolerance: \$0.5 Angular: \$0.5 PD = Paper Down PJ = Paper Down BJ = Burs Down BJ = Burs Up No allowance has been made on the drawing for push through values.