



# HOSHIZAKI

## ADVANCE MD K 120 HG N U

### Multideck refrigerator with Clear Glass End Panels



#### ACCESSORIES INCLUDED

4 stainless shelves

#### OPTIONAL EXTRAS

Price strips, snack baskets, food tray slides

| Energy consumption | Energy efficiency class | Energy efficiency class standard | Energy Efficiency Index (EEI) |
|--------------------|-------------------------|----------------------------------|-------------------------------|
| 5,920.3 kWh/year   | D                       | ISO 23953-1/2:2023               | 43.91 EEI                     |

PRODUCT SERIES: ADVANCE MD 120  
ITEM NUMBER: 211123140  
COUNTRY OF ORIGIN: TURKEY  
BRAND: ADVANCE

Hoshizaki Advance MD K 120 HG N U is a 1200 mm wide open multideck refrigerator with a shelf load capacity (max) of 80kg ranking in energy efficiency class D. It has a cabinet height of 2000-2018 mm including levelling feet and depth of 750 mm.

- Ventilated refrigeration system
- Air circulation system
- Night blind with soft-close feature
- Replaceable end panels
- Tempered and durable glass upstand at front side
- Tempered and durable glass side panels (HG and BG models)
- Exterior and interior of stainless steel AISI 304
- Stainless steel adjustable shelf supports (adjustable by max of 2 levels)
- Shelves can be moved two levels up or down (level distance is 25 mm)
- 4 optional angle positions of shelves from horizontal to a max of 75° angle
- LED lighting integrated underneath each shelf
- Control module can be pulled out at the front side
- Automatic defrost with re-evaporation of defrost water
- Drainage connection not needed
- Integrated levelling feet (4) and wheels (4)
- IP2X water protection

**WARRANTY PERIOD**  
**2 Years on Parts & Labour**

**EXTERIOR**  
**Stainless steel AISI 304**

**INTERIOR**  
**Stainless steel AISI 304**

Refrigerant type: R290 / Refrigerant: 0.333 kg / CO2 equivalent: 0.999 kg

#### CERTIFICATIONS



# ADVANCE MD K 120 HG N U

## TECHNICAL SPECIFICATIONS

| Temperature (Class:<br>3M1 / 3M2) | Shelf size        | Maximum shelf<br>distance | Volume, gross | Net usable volume | Power supply | Connection load | Climate class                                               | Ref. capacity (at<br>-10°C) |
|-----------------------------------|-------------------|---------------------------|---------------|-------------------|--------------|-----------------|-------------------------------------------------------------|-----------------------------|
| -1/+7°C (Class 3M2)               | W 1125 x D 375 mm | 350 mm                    | 730 l         | 530 l             | 230V, 50 Hz  | 1,600 W         | 3 (maximum ambient<br>temperatures of 25 °C<br>with 60% RH) | 2,176 W                     |

## SHIPPING SPECIFICATIONS

| Width (packed) | Depth (packed) | Height (packed) | Volume (packed) | Gross weight | Width    | Depth  | Height   | Net weight |
|----------------|----------------|-----------------|-----------------|--------------|----------|--------|----------|------------|
| 1,300 mm       | 1,000 mm       | 2,150 mm        | 2.8 m3          | 295 kg       | 1,200 mm | 750 mm | 2,000 mm | 250 kg     |

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.

| Maximum shelf load | Maximum shelf can load (can = H120 mm x Ø66 mm) | Maximum bottom tray can load (can = H120 mm x Ø66 mm) |
|--------------------|-------------------------------------------------|-------------------------------------------------------|
| 80 kg              | 80 Pc                                           | 105 Pc                                                |

