

Programable Counter Top Pressure Fryer

Notes

- Do not turn on without oil in the POT.
- Make sure you do not overfill the maximum oil Mark.
- Do not overfill with product, monitor water level in the food product.
- Read the manufacturers Manual.
- The unit smokes and smells when first turned ON. This dissipates after a few minutes.
- It will rise 5C and fall back to set temperature during operation.
- **When the oil is cold. Drain oil from the POT and thoroughly clean daily.**
- The filter between the solenoid should be cleaned on a regular basis, using a spanner to unscrew cap.



Example cook

1.2Kg chicken– cut into 9 pieces, coated	Program – 180C -for 10 mins.
---	-------------------------------------

Programming

1. Make sure there is oil filled to the minimum level in the POT.
2. Press illuminated Power button.
3. Press and hold a Program number. The display will start to flash.
4. Select the Temperature button, and using the increase/decrease arrow buttons set your desired temperature.
5. Select the Timer button, and using the increase/decrease arrow buttons set your desired time.
6. Wait for it to time out or press the Temperature or Timer button.
7. Set up to 5 different temperatures and times.

Operation

1. Make sure there is oil filled to the minimum level in the POT.
2. Press illuminated Power button.
3. Select the desired program number.
4. When the read light next to the temperature display goes out, it will then be ready to use.
5. Using a tiered basket carefully lower it with the coated chicken into the hot oil.

6. Place the lid on and screw down the black restraining fitting, making sure the lid levers are being restrained.
7. Press the Timer picture/icon to start the cook. If you want to stop the cooking process, press the icon again.
8. Wait for the cooking time to elapse. Make sure the pressure **shows zero before you unscrew the lid**. Carefully remove the basket and allow a few minutes hooked on the edge of the POT for the oil to drain and the heat to work through the chicken.