

Opus CombiMaster® Plus

Key Features

- Type: Gas
- Hot air cooking, steam cooking, combination, Finishing
- ClimaPlus Control
- 24 hour digital timer
- Store up to 50 programs with 6 steps
- Powerful steam generator with automatic water refill and automatic self-cleaning function
- Precise core temperature measurement with integral probe
- Airflow optimised cooking cabinet
- Automatic vapour quenching system
- Descaling program
- Manual cleaning program
- Rapid cool down
- Fan speed
- Compatible with GN sizes 1/1, 1/2, 2/3, 1/3, 1/4
- Auto alerts when service required
- Simple to use, repeatable results, reliable, save time and costs
- Integral hand shower



OCMP61 /N & P

Construction

- Body: stainless steel grade 304
- Oven liner: stainless steel type 304
- CrNi steel DIN 1.4301

Available Options



















- Left hinged door (selected models)
- Integral fat drain (selected models)
- Hinging rack for bakery option
- Hand shower
- Detergent spray gun
- Safety door lock
- Marine version
- Security/Prison version
- Lockable control panel
- Connection to serial interface

Available Accessories

- Stands and base cabinets
- Mobile oven rack for GN containers
- Transport trolley
- Mobile banqueting plate rack
- CombiDuo stacking kits
- Exhaust hood
- Thermocover insulating hood
- Cleaner tablets and rinse aid tablets
- CombiLink
- Banqueting Finishing® system
- GN containers, grids, trays
- Chicken grid & Duck grid
- CombiFry basket
- GriddleGrid
- Grease drip collector
- Potato Baker
- MultiBaker
- Grill & Pizza Tray

Specifications

Model	OCMP61/N/P	OCMP62/N/P	OCMP101/N/P	OCMP102/N/P	OCMP201/N/P	OCMP202/N/P
Capacity (1/1GN)	6	12	10	20	20	40
No. of meals per day	30 - 80	60 - 160	80 - 150	150 - 300	150 - 300	300 - 500
External height (mm)	782	782	1042	1042	1782	1782
External width (mm)	847	1069	847	1069	879	1084
External depth (mm)	771	971	771	971	791	996
Net weight unpacked (kg)	121	159	148	190	252	370
Gross weight packed (kg)	151	199	185	237.5	312	462.5
Shipping volume (m ³)	0.83	1.06	1.06	1.1	2.03	3.14
Water pressure (kPa)	150 – 600	150 – 600	150 – 600	150 – 600	150 – 600	150 – 600
Water connection (BSP)	3/4	3/4	3/4	3/4	3/4	3/4
Heat input Natural (kW)	13	28	22	45	44	90
Heat input Propane (kW)	14	31	24	50	48	100
Gas consumption at full rate Natural (m ³ h ⁻¹)	1.05	2.05	2.05	3.05	4.1	6.1
Gas consumption at full rate Propane (kg h ⁻¹)	0.86	1.64	1.64	2.43	3.29	4.8
Gas inlet	G ½ female	G ½ female	G ½ female	G ½ female	G ½ female	G ½ female
Btu/h conversion	kW x 3412	kW x 3412	kW x 3412	kW x 3412	kW x 3412	kW x 3412



Lincat Limited, Whisby Road,
Lincoln LN6 3QZ,
United Kingdom

UK Sales Tel: 01522 875500 UK Spares Tel: 01522 875510 UK General Tel: 01522 875555
UK Fax: 01522 875530 International Sales Tel: +44 1522 503250 International Fax: +44 1522 875530
Website: www.lincat.co.uk UK Sales e-mail: sales@lincat.co.uk International Sales e-mail: export@lincat.co.uk



Document ref: OCMPGAS
Issue date: Oct-11