



REVERSE OSMOSIS DEVICE OS-140P



SPECIFICATIONS

Membranes: 4 x TWG1A1
Internal pre-filter: Profine BLUE small
Total loading: 180 W

Water flow data

- ✓ Maximum water inlet flow: 300 l/h
- ✓ Maximum temperature: 35 °C
- ✓ Feed water pressure (bar) (max): 5 bar
- ✓ Feed water pressure (bar) (min): 1.5 bar

Permeate specifications

- ✓ ___ Maximum capacity (10°C): 140 l/h
- ✓ Recovery percentage: 25-60%

Noise level (1m.): <70 dB(A)
External dimensions (WxDxH): 168 mm x 515 mm x 476 mm
Net weight: 20 Kg

AVAILABLE MODELS

5320140 Reverse osmosis device OS-140P 230/50/1

6320220 Small blue filter for osmosis

* Ask for special versions availability

SALES DESCRIPTION

Reverse osmosis equipment for industrial, professional and catering applications.

Simplicity and speed.

Suitable for dishwashers with or without a break tank.

Reverse osmosis provides excellent finish, specially in glassware, and accelerates the drying process of the wares.

- ✓ The purifier ensures a high and immediate flow which, combined with high pressure, allows fast and continuous washing cycles.

WARE WASHING
OSMOSIS WATER PURIFIER



www.sammic.co.uk

Food Service Equipment Manufacturer
Unit 2, Trevanth Road
Troon Industrial Park
LE4 9LS - Leicester
uksales@sammic.com
Tel.: +44 0116 246 1900



Project	Date
Item	Qty
Approved	

product sheet
updated 01/02/2021