

DISHWASHER UX-100B 230/50/1 DD

Rack size 500x500mm and door clearance 430 mm.

Designed to last

P/N 1303324



SALES DESCRIPTION

Sani-Control: guaranteed disinfection Exclusive Hydroblade™ washing arms: maximum effectiveness.

3-stage filtering system.

Sani-Control guarantee

- GUARANTEED DISINFECTION in compliance with standard DIN 10534
- √ THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.

New recessed bodywork

- Ergonomic design with rounded corners to prevent the accumulation of dirt and facilitate cleaning.
- Compact tank volume (50% water saving compared to the previous range).

Hydroblade™ washing arms

- Redesigned nozzles for greater washing performance.
- √ The "monoblock" design delivers durability and resistance to impacts.
- √ 30% savings in water consumption during rinsing compared to the

3-stage filter system: surface, tank and extraction

√ Keeps the washing water in optimal conditions to maintain constant

washing performance.

- √ "Flow" opening mechanism: allows the hood to be raised with less
- √ High load capacity 43 cm: suitable for GN 1/1 and Euronorm
- Stainless steel surface filters for greater stability and resistance during intensive use

Premium warewashing

- Soft start: progressive start-up of the washing pump to protect fragile items.
- Colour LCD Display: intuitive communication of the machine status by means of messages, colour codes and icons.
- Dedicated cycles: selection of the ideal washing programme using icons.
- Adaptable: allows the main parameters of the machine to be adjusted to the needs of each user.
- √ TEMPERATURE DISPLAY
- Wash Plus+ function: increases the intensity of the wash cycle for greater cleaning performance
- Control panel with IP65 humidity protection.

You will never WASH ALONE

- Tech-Services: our team of technicians will help you so that your machine is always ready for use.
- ✓ Design Services: tell us what your needs are and we will advise you.
- √ 60 years of experience and know-how at your disposal.

Detergent Dispenser 1 glasses basket. 1 mixed basket (plates). 1 cutlery basket.

NCLUDES

- Drainage pump with level sensor. Proactive tank water renewal.
- Detergent dispenser..
- √ 1 glasses basket.
- √ 1 mixed basket (plates).
- 1 cutlery basket.

Accessories

- ☐ Tables for dishwashers P/X/S (pass-through model)
- Manual water softeners
- Automatic water softeners
- □ 500 x 500 mm, baskets
- □ Inserts & supplements
- Central sorting tables
- Double connection central sorting table
- Prewashing tables for pass-through and rack convevor
- Connecting tables for Pass-Through dishwashers and rack conveyors
- ☐ Reverse Osmosis device OS-140P
- Dosing equipments









www.sammic.co.uk

Food Service Equipment Manufacturer Unit 2. Trevanth Road Troon Industrial Park LE4 9LS - Leicester

uksales@sammic.com Tel.: +44 0116 246 1900



Project	Date
Item	Qty

Approved

WARE WASHING WASHING WASHING

<u> </u>

DISHWASHER UX-100B 230/50/1 DD

Rack size 500x500mm and door clearance 430 mm.

P/N 1303324

SPECIFICATIONS

Basket dimensions: 500 mm x 500 mm Maximum glass height: 430 mm

Cycles: 6

Cycle duration: -- "/--"/--"
Production baskets/hour: --/--/--

Boiler capacity: -- I Wash tank capacity: 25 I

Consumption and savings

- √ Water consumption/cycle: 3 I
- ✓ Automatic saving mode in: 25 '
- ✓ Automatic switch-off: 120 '

Loading

- ✓ Pump: -- W / -- Hp
- √ Tank: 2500 W
- ✓ Boiler: 7500 W
- √ Total loading: 8200 W

Electrical supply: 230 V / 50 Hz / 1 \sim (37 A)

External dimensions (WxDxH)

- √ Width:648 mm (: -- mm)
- ✓ Depth: 756 mm (: -- mm)
- √ Height: 2000 mm / 1510 mm

Net weight: 103 Kg

Wash temperature: 65 °C Rinse temperature: 87 °C

Net weight: 103 Kg

Noise level (1m.): <70 dB(A)

Crated dimensions

760 x 860 x 1960 mm Gross weight: 114 Kg.



www.sammic.co.uk

Food Service Equipment Manufacturer Unit 2, Trevanth Road Troon Industrial Park LE4 9LS - Leicester

uksales@sammic.com Tel.: +44 0116 246 1900



Project	Date
Item	Qty

Approved