

Pro 16 Tray Counter PRO16DR



Temperature Retarder -4/4 °C						
Dimensions (mm)						
W 1825 D 916						
H 863						
Capacity						
Unpacked Weight						
123 KG						

Features & Benefits

The Foster Bakery Range helps you plan and prepare your production to overcome the peaks and troughs associated with every bakery, ensuring you make the very best use of your time and available storage space.

- State of the art design giving the reliability, energy efficiency and performance you expect from Foster
- Variable retarding temperature options between $-4\frac{p_1}{r}$ and $+4\frac{p_2}{r}$ C
- Automatic humidity control prevents skinning and weight loss
- Sophisticated airflow system ensures even temperature and humidity throughout
- High Quality 304 Stainless Steel Exterior Build Quality

External Finish		Doors		Electrical Data & Service	
304 Stainless Steel	Standard	Solid Full	Standard	Information	
Internal Finish		Refrigeration		230 Volts	Standard
		Reingeration		50Hz	Standard
304 Stainless Steel	Standard	Forced Air	Standard	1 Phase	Standard
		Integral	Standard	Running Watts	325
Shelving		R134a	Standard	Running Amps	2.2
Bakery Capacity: 16	Standard	Drain Required?	No	Thermal Heat Rejection	363
Tray-				(W)	
30x18				Noise (dBa @ 1m)	ТВС
Bakery Capacity: 16	Option			Fuse Required (A)	10 amp
Tray-					
60x40					
Base Fittings					
80mm Castors	Standard				

Footnotes

- Bakers trays not supplied as standard
- All the above models are built to take 30" x 18" trays as standard. If it is required to take 60 x 40 cm trays, please specify this at the time of ordering by adding a 'C' prefix eg. C PRO 20 DR
- Extra pairs of stainless steel trayslides available

Foster-Fridge.com

Telephone: 01582 865050 Facsimile: 01582 645947 Email: info@foster-fridge.com













ISO 14001



Demand more. Choose Foster

REFRIGERANT