





MANUFACTURER

HALLDE

MODEL

RG-250

PRODUCT DESCRIPTION

Vegetable Preparation Machine, process up to 8 kg/minute.

ORIGIN

Sweden

SPECIFICATION					
SPECIFICATION TEXT	Vegetable preparation machine with leaning design and full moon feed cylinder, made to process 8 kg/minute or 50-800 portions/day. Machine has aluminium pusher plate with loop shaped stainless steel handle and a tube feeder of 56 mm in diameter. Pusher plate with system for leverage effect. Four litre feed cylinder with 55 mm inner wall. Cutting tools are made of stainless steel/aluminium/ acetal with removable knifes/plates and are 185 mm in diameter. Motor rotate the cutting blade clockwise and direct without intermediate belts.				
FUNCTION	Machine for slicing, dicing, shredding, grating, cutting julienne and French fries. Processes fruit, vegetables, dry bread, cheese, nuts, mushrooms, etc.				
CAPACITY	Up to 800 portions/day and up to 8 kg/minute. 4 liter feed cylinder, 56 mm tube feeder for elongated products.				
MATERIAL	Machine base and feed cylinder: aluminium alloy. Push handle: stainless steel. Cutting tools: stainless steel/aluminium/fiberglass reinforced polyamide. Ejector plats: acetal.				
MOTOR	0.55 kW. One-speed (350 rpm) 120 V, 1-phase, 60 Hz. 220-240 V, 1-phase, 50/60 Hz. 230-240 V, 3-phase, 50 Hz. 400 V, 3-phase, 50/60 Hz. 440 V, 3-phase, 60 Hz. Thermal protection, Planetary gearing.				
POWER SUPPLY	Earthed, single phase, 10 A / three phase, 16 A. Fuse: 10 A delayed action fuse.				
STANDARDS	EN 1678+A1:2010. NSF/ANSI Standard 8.				
RECOMMENDED CUTTING TOOL PACKAGES	INCLUDING				NET WEIGHT
	 4-pack Cutting Tools Slicer 1.5 mm Grater/Shredder 2 mm Slicer 4 mm Grater/Shredder 8 mm 				2 kg
	7-pack Cutting Tools Slicer 1.5 mm				3,5 kg
WEIGHT/VOLUME	CONTENT	NET WEIGHT	PACKAGES	FREIGHT WEIGHT	FREIGHT VOLUME
	RG-250 Machine	22 kg	1	25 kg	0.183 m³
	Container Trolley incl. GN 1/1 container	9 kg	1	12.5 kg	0.15 m ³
	Machine Table incl. GN 1/1 container	13,25 kg	1	14,5 kg	0,8 m³
SAFETY	2014/30/EU, 2014/35/EU, 2006/42/EG, 2011/65/EU, no 10/2011				
DIRECTIVE AND REGULATION	CE approved. Two safety switches, machine safety: IP44, push buttons safety: IP65.				

