





MANUFACTURER

HALLDE

MODEL

RG-350

PRODUCT DESCRIPTION

Vegetable Preparation Machine, process up to 30 kg/minute.

ORIGIN

Sweden

	Si	PECIFICATION			
SPECIFICATION TEXT	Vegetable preparation machine with leaning design and full moon feed cylinder, made to process 12-30 kg/minute or 400-1 200 portions/day. Machine has aluminium pusher plate with loop shaped stainless steel handle and a tube feeder of 59 mm in diameter. Pusher plate with system for leverage effect. Stainless steel feed hopper as an alternative. 5.7 litre feed cylinder with 62 mm inner wall. Cutting tools are made of stainless steel/aluminium with removable knifes/plates and are 215 mm in diameter. Motor rotate the cutting blade clockwise and direct without intermediate belts.				
FUNCTION	Machine for slicing, dicing, shredding, grating, cutting julienne and French fries. Processes fruit, vegetables, dry bread, cheese, nuts, mushrooms, etc.				
CAPACITY	Up to 1 200 portions/day and up to 30 kg/minute. 5.7 liter feed cylinder, 59 mm tube feeder for elongated products.				
MATERIAL	Machine base and feed cylinder: aluminium alloy. Push handle and Feed Hopper: stainless steel. Cutting tools: Stainless steel/ Aluminum.				
MOTOR	0.75 kW. One-speed (360 rpm) Manual Feeder: 220-240 V, 1-phase, 50-60 Hz. 220-240 V, 3-phase, 50-60 Hz. 120 V, 1-phase, 60 Hz. 380-415 V, 3-phase, 50 Hz. 440-460 V, 3-phase, 60 Hz. Feed Hopper: 220-240, 1-phase, 50-60 Hz. 380-415, 3-phase, 50 Hz. Thermal protection, Planetary gearing.				
POWER SUPPLY	Earthed, single alt. three phase, 10 A / three phase, 16 A. Fuse: 10 A delayed action fuse.				
STANDARDS	EN 1678+A1:2010. NSF/ANSI Standard 8.				
RECOMMENDED CUTTING TOOL PACKAGES	INCLUDING				NET WEIGHT
	6-pack Cutting Tools Slicer 1.5 mm				6 kg
	9-pack Cutting Tools Slicer 1.5 mm				9 kg
WEIGHT/VOLUME	CONTENT	NET WEIGHT	PACKAGES	FREIGHT WEIGHT	FREIGHT VOLUME
	RG-350 Machine	32 kg	1	36 kg	0.198 m³
	Container Trolley incl. GN 1/1 container	9 kg	1	12.5 kg	0.15 m ³
	Machine Table incl. GN 1/1 container	13,25 kg	1	14,5 kg	0,8 m³
SAFETY	2014/30/EU, 2014/35/EU, 2006/42/EG, 2011/65/EU, no 10/2011				
DIRECTIVE AND REGULATION	CE approved. Two safety switches, machine safety: IP44, push buttons safety: IP65.				

