





MANUFACTURER

HALLDE

MODEL

RG-50

PRODUCT DESCRIPTION

Vegetable Preparation Machine, process up to 2 kg/minute.

ORIGIN

Sweden

| | S | PECIFICATION | | | |
|---|---|--------------|----------|----------------|----------------------|
| SPECIFICATION TEXT | Table top vegetable preparation machine with half-moon feed cylinder, made to process 2 kg/minute or 10-80 portions/day. Machine has polycarbonate and polyamide feed top of 0.9 litre and a tube feeder of 53 mm in diameter. Machine base is made of ABS-plastic and the knife chamber of aluminium. Machine is controlled with a turning knob instead of buttons. Cutting tools are made of stainless steel, 185 mm in diameter and washable in dishwasher. Motor rotate the cutting blade clockwise via a self-tensioned toothed belt. Machine has handles for easy mobility. | | | | |
| FUNCTION | Machine for slicing, dicing, shredding, grating and cutting julienne. Processes fruit, vegetables, dry bread, cheese, nuts, mushrooms, etc. | | | | |
| CAPACITY | Up to 80 portions/day and up to 2 kg/minute. 0.9 liter feed cylinder, 53 mm tube feeder for elongated products. | | | | |
| MATERIAL | Machine base: ABS-plastic. Knife chamber: aluminium. Feeder top: polycarbonate and polyamide. Cutting tools: stainless steel. Ejector plate: acetal. | | | | |
| MOTOR | 1.0 kW. One-speed (500 rpm) 220-240, 1-phase, 50/60 Hz. 120, 1-phase, 60 Hz. Transmission: Toothed belt. Thermal protection. | | | | |
| POWER SUPPLY | Earthed, single phase, 10 A. Fuse: 10 A delayed action fuse. | | | | |
| STANDARDS | EN 1678+A1:2010. NSF/ANSI Standard 8. | | | | |
| RECOMMENDED CUTTING TOOL PACKAGES | INCLUDING | | | | NET WEIGHT |
| | 2-pack Cutting Tools Slicer 4 mm - Grater/Shredder 4 mm | | | | 0,6 kg |
| | 4-pack Cutting Tools Slicer 2 mm Slicer 4 mm Julienne Cutter 2x2 mm | | | | 1.2 kg |
| WEIGHT/VOLUME | CONTENT | NET WEIGHT | PACKAGES | FREIGHT WEIGHT | FREIGHT VOLUME |
| | RG-50 Machine | 9 kg | 1 | 11 kg | 0.097 m ³ |
| SAFETY | 2014/30/EU, 2014/35/EU, 2006/42/EG, 2011/65/EU, no 10/2011 | | | | |
| DIRECTIVE AND REGULATION | CE approved. Two safety switches, machine safety: IP34. | | | | |
| DRAWINGS | The drawings below can be downloaded at hallde.com. | | | | |
| | 350 | 285 | | 585 465 150 | 405 |