



# LABCOLD™

medical & scientific refrigeration



Why not prolong the life of your Labcold Blood Bank by asking about Maintenance Contracts when you place your order?

**FREE 2**  
**YEAR WARRANTY**  
LABCOLD

Fitted with a Dual Compressor to ensure greater temperature control and peace of mind in the event of failure of one of the systems. Each complete refrigeration system provides 100% performance, sufficient to cool down and maintain temperatures correctly without help from the second compressor.



Hygienic touch screen controller



An asymmetric change over ensures even distribution of workload, resulting in even wear of the compressors and also allows for one to defrost while the other is still running. The two independent systems provide back up should an issue develop plus there is no need to move contents immediately if a problem is identified. We also supply a range of blood baskets purpose made for shelf models. These are designed for good air circulation around the product while keeping labels visible for ease of access and organisation. Designed and manufactured in the UK in our Basingstoke factory, this Blood Bank refrigerator is a certified Medical Device in accordance with Directive 93/42/EEC and is compliant with BS4376:Part 1:1991.

Labcold blood banks are tested for 72 hours and calibrated before they are dispatched and all come with a FREE 2 year parts and labour warranty.

## RSBG2540MD Freestanding Dual Compressor Blood Bank

| Part Number  | RSBG2540MD                         |
|--|------------------------------------|
| Capacity (Litres)  | 1245                               |
| Capacity (250ml bags)  | 600 (approx)                       |
| Style  | Freestanding                       |
| Exterior Dimensions (HxWxD)                                      | 1980 x 1440 x 840mm                |
| Interior Dimensions (HxWxD)                                      | 1420 x 1310 x 675mm                |
| Weight   | 365kg                              |
| Energy Consumption   | 5.5 kWh/24h                        |
| Operating Temperature  | +4°C +/- 2°C                       |
| Interior Construction  | Stainless Steel                    |
| Exterior Construction  | Powder Coated Steel                |
| Door Style   | Glass                              |
| Door Hinging   | Double                             |
| Dual Refrigeration   | ✓                                  |
| Open Door alarm  | ✓                                  |
| Load Temperature Alarm   | ✓                                  |
| Air Temperature Alarm  | ✓                                  |
| Mains Failure Alarm  | ✓                                  |
| Air Temperature Display  | ✓                                  |
| Load Temperature Display   | ✓                                  |
| 7 Day Chart Recorder   | ✓                                  |
| Lock   | Digital Keypad                     |
| Battery Back Up  | ✓                                  |
| Shelves  | 12                                 |
| Baskets (optional extra)   | Max 10 x BABB4007<br>50 x BABB5610 |
| Remote alarm contacts  | ✓                                  |
| Access Port  | ✓                                  |
| Auto Defrost   | ✓                                  |
| Internal Light   | ✓                                  |
| Eco Friendly Refrigerant   | ✓                                  |
| Certified Medical Device in Accordance with Directive 93/42/EEC. | ✓                                  |

01256 705 570

[www.labcold.com](http://www.labcold.com)

