product sheet updated 30/06/2022



COMBI VEGETABLE PREP.-CUTTER CK-35V 230/50-60/1

2 in 1: vegetable cutter (450 kg/h) + cutter with 5.5 lt bowl.

1050752



quality: stainless steel motor block and food-grade aluminium head. Stainless steel hopper with highly-resistant polycarbonate lid.

Maximum comfort for the user

- Ergonomic design: product sliced in one single movement.
- Lateral product output: it requires less room on the work surface and directs the product avoiding splashing.
- Advanced control panel that is very intuitive to use and offers all the information at a glance.

Maintenance, safety, hygiene

- ✓ Plunger, lid and bowl easy to remove for changing or cleaning.
- √ Combination of security systems: head, covers, bowl, power switch.
- Appliance certified by NSF International (regulations on hygiene, cleaning and materials suitable for contact with foods).
- √ 100% tested.

NCLUDES

- √ Variable speed motor block.
- √ Universal head.
- Cutter bowl, with micro-serrated blade rotor.

OPTIONAL

- ☐ Tube head.
- ☐ Discs, grids and disc support.
- ☐ Rotor with smooth cutting blades.
- Rotor with perforated cutting blades.
- Support-trolley.
- Grid cleaning kit.

ACCESSORIES

- ☐ FCC Curved Slicing Discs
- ☐ FCO Rippled Slicing Discs
- ☐ FFC Chipping Grids
- ☐ FMC Dicing Grids
- ☐ FCE Julienne Discs
- ☐ FR Shredding & Grating Discs
- ☐ Disc and Grid Holder
- □ Blades for CK / K / KE
- □ Grid Cleaning Kit
- □ FC-D Slicing Discs
- $\hfill \square$ SH Shredding & Grating Discs

SPECIFICATIONS

Total loading: 1500 W

Electrical supply: 230 V / 50-60 Hz / 1 \sim (10 A)

Plug: EU (SCHUKO 2P+G)

As vegetable preparation machine

Hourly production: 100 Kg - 450 Kg

Inlet opening: 136 cm² Disc diameter: 205 mm

Speed as veg. slicer: 300 rpm - 1000 rpm

External dimensions (WxDxH): 391 mm x 409 mm x 552 mm

Net weight (Veg.Prep.):24 Kg

As cutter

Bowl capacity: 5.5 l

Speeds as cutter (positions): 300 rpm - 3000 rpm

External dimensions (WxDxH):286 mm x 387 mm x 487 mm

Net weight (Cutter): 18 Kg Noise level (1m.): <70 dB(A) Background noise: 32 dB(A)

Crated dimensions

705 x 415 x 515 mm Volume Packed: 0.15 m³ Gross weight: 31.8 Kg

Equipped with "brushless" technology: powerful and efficient motors.

It has a variable speed motor block, universal head and

5.5-It cutter bowl equipped with a rotor with micro-se-

- Maximum efficiency: maintain the torque throughout the speed range
- Exclusive "force control system": guarantee of a uniform and high quality result.
- ✓ Lightweight and compact design: they weigh less, they occupy less space.
- ✓ Improved air/water-tightness since no ventilation is required.
- ✓ They generate less noise: improved workplace environment.

Cutting function: a perfect cut

SALES DESCRIPTION

Brushless technology.

rrated blades.

- High precision settings and comprehensive cutter and disc design aimed at obtaining a perfect cut.
- It can be fitted with a wide range of discs and grids of the highest cutting quality. Combining these accessories together to obtain more than 70 different types of cuts and grating grades.
- Exclusive "Force Control System" to optimise and standardise the cutting of each product: acoustic warning when the motor exceeds the pre-established force.

Cutter function: efficiency and performance

- Possibility of programming by time and pulse button.
- ✓ Reverse function, ideal for mixing products instead of cutting.
- √ 5.5 It stainless steel bowl.
- ✓ Polycarbonate lid with built-in "cut&mix" mixer.
- Depending on the purpose, the possibility of using optional smooth or perforated blades.

Built to last

√ Made from stainless steel and food-grade materials of the highest










COMBI VEGETABLE PREP.-CUTTER CK-35V 230/50-60/1


2 in 1: vegetable cutter (450 kg/h) + cutter with 5.5 lt bowl.

1050752











www.sammic.co.uk

Food Service Equipment Manufacturer Unit 2, Trevanth Road Troon Industrial Park LE4 9LS - Leicester

uksales@sammic.com Tel.: +44 0116 246 1900



Project	Date
Item	Qty

Approved