



1-DOOR FREEZER CABINET, HC SNOWFLAKE G II SUF-65DG-R-C U

Product series: Snowflake GII

Item number: 877010865

The <u>Snowflake GII series</u> is brought to you by Japanese and Danish engineering excellence, dedicated to simplifying the day-to-day work routines of kitchen staffs all around the world.

The technology behind the performance boost of Snowflake GII is the <u>tropicalised cooling system</u> enduring up to +40°C. Additionally, the cooling agent of the new generation of Snowflake is the <u>ecofriendly refrigerant R290</u>, a natural gas (HC) that enhances the performance and cuts down energy consumption significantly.

The <u>Snowflake GII SUF-65DG-R-C U</u> is a 1 door freezer cabinet with a net internal volume of 398 Ltr.

As a product that is designed and built to last, this freezer cabinet combines an innovative design concept, premium materials and clever extras:

- <u>Minimum cool air lost</u>: double insulated and extra wide door gaskets help to keep the cold air into the cabinet
- Anti-tilt mechanism: moulded liners for saver container and rooster handling
- Reversible doors for maximum flexibility
- Removable gaskets make sure you can clean the device thoroughly
- This and other thoughtful extras, such as the cleaning-free condenser, are designed to reduce kitchen cleaning times whilst storing foods protectively in the best possible way

The refrigerant used in all Snowflake GII HC models is R290.

This agent is a natural gas which enhances the performance of the refrigerated counter and has, compared to other refrigerants, a minimal ozone depletion potential.

SPECIFICATIONS

| Product title | 1-DOOR FREEZER CABINET, HC |
|---------------------------|----------------------------|
| Temperature range | -10/-20°C |
| Internal volume gross (I) | 560 |
| Net usable volume (I) | 398 |
| Net weight (kg) | 115 |
| Gross Weight Packed (kg) | 140 |
| Climate class | 5 |
| Energy label | D |

| Interior | Stainless steel |
|---|------------------|
| Exterior | Stainless steel |
| Number of shelves | 3 |
| Energy Consumption (kWh/24hrs) at 32.2°C ambient and 65% RH | 7.01 |
| Electric connection Load (kW) | 0.4 |
| Electric connection | 230V, 1N-/50 Hz |
| Outside Dimensions W x D x H (mm) | 654 x 840 x 1996 |
| Refrigerant | R290 |

Hoshizaki Europe B.V. Headquarters Export EMEA, Burgemeester Stramanweg 101, 1101 AA Amsterdam, the Netherlands, T: +31 (0)20 565 0429 sales@hoshizaki.nl - www.hoshizaki-europe.com