



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R404A / R507**

| Specifications | SUMBA 1.0 | SUMBA 1.5 | SUMBA 2.0 | SUMBA 2.5 |
|--|-----------|-----------|-----------|--------------|
| CODE | SU100 | SU101 | SU102 | SU103 |
| Length [mm] | 1060 | 1500 | 2040 | 2520 |
| Length with the sides [mm] | 1060 | 1500 | 2040 | 2520 |
| Capacity [dm ³] | 120 | 195 | 260 | 335 |
| Usable storage capacity [dm ³] | 120 | 210 | 290 | 370 |
| The area of shelves [m ²] | 0,65 | 0,95 | 1,3 | 1,61 |
| Side panel thickness [mm] | 40 | 40 | 40 | 40 |
| Depth [mm] | 940 | 940 | 940 | 940 |
| Height [mm] | 1260+/10 | 1260+/10 | 1260+/10 | 1260+/10 |
| Unit weight [kg] | 160 | 206 | 258 | 320 |
| Refrigerant/Cooling factor | R134a | R134a | R134a | R404A / R507 |
| Evaporating temperature [°C] | -15 | -15 | -15 | -15 |
| Cooling power demand [W/mb] | 350 | 350 | 350 | 350 |
| Rated voltage [V] | 230/50Hz | 230/50Hz | 230/50Hz | 230/50Hz |
| Rated power of lighting [W] | 8,5 | 17 | 22,4 | 31,4 |
| Rated power [W] | 242 | 307 | 392 | 588,4 |
| Cooling power [W] | 411 | 547 | 710 | 947 |
| Electricity consumption [kWh/24h] | 3,4 | 4,3 | 5,5 | 8,2 |

Standard equipment

internal cooling aggregate

device prepared for multiplexing

static cooling (2 evaporators)

body with service - side base flashing composed of white, coated sheet metal

front base sheets and front panel with color-coated sheet - selectable color (IGLOO color guide)

ecological polyurethane foam insulation

exposition area made of stainless steel

storage chamber made of white coated steel

rear storage compartment door - sliding (in the module 1.0 and corners - hinged)

grey granite worktop (thickness 20 mm)

internal frame and aluminum profiles anodised color silver or gold (IGLOO pattern book)

straight front glass pane (which can slightly be opened)

night blinds made of plexi glass

LED lamp (color of choice: white, confectionery or meaty "deep pink")

insulated plastic side walls + glass side panels - different colors available (IGLOO pattern book)

automatic defrost

automatic condenser vaporization

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

Options

insulated plastic sides + glass sides - selectable colour (IGLOO colour chart)

wooden sides + glass sides - selectable colour (IGLOO colour chart)

device without side panels prepared for multiplexing (MOD/A)

hinged system for the front window

housing with base panel from staff side made of stainless steel

front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)

front panel color - different colors available (IGLOO pattern book)

custom front panel color (after consultation with the IGLOO Sales Department)

base panel made of stainless steel

exposition area made of acid resistant stainless steel

storage chamber made of stainless steel

storage chamber made of acid - resistant stainless steel

exposition stepped overlay made of stainless steel (1 step)

exposition stepped overlay made of acid resistant stainless steel (1 step)

exposition stepped overlay made of stainless steel (2 step)

exposition stepped overlay made of acid resistant stainless steel (2 step)

powder painted evaporator

worktop - granite Balmoral (thickness : 20 mm)

worktop - granite black (thickness : 20 mm)

worktop - stainless steel

additional exposition glass shelf with illumination - LED light

set of wheels (castors)

automatic defrost

electronic temperature recorder + software

recorder cable

socket with fuse

customer front shelf (aluminum profile anodised color silver or gold)

front shelf for the customer with wooden profiles and stainless steel inserts - selectable colour (IGLOO colour chart)

movable partition (low ,glass on stands , placed in exposition area)

top fixed partiton (high , glass in exposition area)

runner for small movable table

small movable table for scale or cash register (400x500mm)

