



2-DOOR REFRIGERATED CABINET, HC SUR-135DG-R-C U

Product series: Snowflake GII

Item number: 878000865



The Snowflake GII series is brought to you by Japanese and Danish engineering excellence, dedicated to simplifying the day-to-day work routines of kitchen staffs all around the world.

The technology behind the performance boost of Snowflake GII is the tropicalised cooling system enduring up to +40°C. Additionally, the cooling agent of the new generation of Snowflake is the eco-friendly refrigerant R290, a natural gas (HC) that enhances the performance and cuts down energy consumption significantly.

Both interior and exterior are built of anti-corrosion stainless steel, which is among the best choices for hygienic and food safe cooking environments.

The Snowflake GII SUR-135DG-R-C U is a 2-door refrigerated cabinet with a net internal volume of 810 Ltr.

As a product that is designed and built to last, this freezer cabinet combines an innovative design concept, premium materials and clever extras:

- Minimum cool air lost: double insulated and extra wide door gaskets help to keep the cold air into the cabinet
- Anti-tilt mechanism: moulded liners for saver container and rooster handling
- Reversible doors for maximum flexibility
- Removable gaskets make sure you can clean the device thoroughly
- This and other thoughtful extras, such as the cleaning-free condenser, are designed to reduce kitchen cleaning times whilst storing foods protectively in the best possible way

The refrigerant used in all Snowflake GII HC models is R290. This agent is a natural gas which enhances the performance of the refrigerated counter and has, compared to other refrigerants, a minimal ozone depletion potential.

SPECIFICATIONS

Product title	2-Door Refrigerated Cabinet, HC
Temperature range	-2/+8°C
Internal volume gross (l)	1310
Net usable volume (l)	810
Net weight (kg)	176
Gross Weight Packed (kg)	220
Climate class	5
Energy label	D

Interior	Stainless steel
Exterior	Stainless steel
Number of shelves	6
Energy Consumption (kWh/24hrs) at 32.2°C ambient and 65% RH	3.97
Electric connection Load (kW)	0.32
Electric connection	230V, 1N-/50 Hz
Outside Dimensions W x D x H (mm)	1344 x 840 x 1996
Refrigerant	R290