





SINGLE FLAVOR, COUNTERTOP, GRAVITY FEED



Ultra high output and perfect solution for **alcoholic** and **non-alcoholic** frozen beverages, suitable for all sectors across the hospitality industry



FREEZE DOWN

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption



SIMPLE CONTROL, EASY OPERATION

Simple and intuitive control system makes operation easy and swift



LOW MIX INDICATOR

Light turns "ON" at low mix to alert operator to add mix



TRANSPARENT DISPENSING DOOR

Clear dispensing door design makes product more attractive and serves as great marketing tool



DISPENSING

Fast and easy dispense to keep up with demand and maintain profit margins



STANDBY

Maintains product temperature in both mix hopper and freezing cylinder below 4.4 $^{\circ}$ C (40 $^{\circ}$ F) overnight



SAFETY PROTECTIONS

- High pressure switch to prevent compressor overheating
- Thermal overload to protect from motor overheating


MOST COMPACT & VERSATILE SINGLE FLAVOUR DISPENSE UNIT FOR FROZEN BEVERAGE AND SMOOTHIES






MODEL T420

FROZEN BEVERAGE FREEZER MACHINE





















SPECIFICATIONS

| Flavours | 1 |
|-------------------------|------------------|
| Freezing Cylinders | 1 x 3.2L |
| Mix Hoppers | 1 x 25L |
| Output Capacity (250ml) | 80 serves/hr |
| Clearance Requirements | 152mm/6" on left |
| | |

| WEIGHT | KG/LB (Gravity) | KG/LB (Pump) |
|----------|-----------------------|--------------|
| Net | 139 / 309 | 144 / 320 |
| Shipping | 152/ 338 | 157 / 349 |
| Volume | 0.47 CBM / 1 6.62 CBF | |

| DIMENSIONS | NET (MM/IN) | SHIPPING (MM/IN) |
|------------|-------------|------------------|
| Width | 454 / 17.9 | 500 / 19.7 |
| Depth | 580 / 22.8 | 770 / 30.3 |
| Height | 734 / 28.9 | 890 / 35.0 |

| ELECTRICAL | AMP | VOLT | POWER(KW) |
|----------------|-----|------|-----------|
| 110-1 1 5/60/1 | 13 | NA | NA |
| 220-240/50/1 | 13 | NA | NA |

FEATURES

| CONTROL SYSTEMS | SINGLE MECHANICAL |
|--------------------------------|-------------------|
| REFRIGERATED HOPPERS | V |
| HOPPER AGITATOR | V |
| TEMPERATURE DISPLAY | |
| STANDBY MODE | V |
| AUTO CLOSING DISPENSING VALVES | |
| DISPENSING SPEED CONTROL | |
| LOW MIX INDICATOR LIGHT | V |
| LOW MIX INDICATOR ALARM | V |
| LOW TEMPERATURE PROTECTION | V |
| MOTOR AMPERAGE PROTECTION | V |
| HIGH PRESSURE PROTECTION | V |
| THERMAL OVERLOAD PROTECTION | ✓ |
| | |