



British Manufacturing  
since 1957



*The Professionals Choice*

## UCB47

InstaTap Under Counter Hot Water Boiler



## FULL SPECIFICATION



### UCB47 InstaTap Under Counter Hot Water Boiler

Type	Under-counter range – <i>Push-button Hot Water Dispenser</i>
Country of Design & Manufacture	UK
<b>CAPACITY, WEIGHTS &amp; DIMENSIONS:</b>	
Capacity (Litres)	47
Unit dimensions (W x D x H) mm	465 x 500 x 560
Packed dimensions (W x D x H) mm	590 x 600 x 1045
Product weight (c/w dispense font) empty (kg)	25.3
Product weight (c/w dispense font) full (kg)	67.0
Packed weight (c/w dispense font) (kg)	37.0
<b>CONSTRUCTION (UC unit):</b>	
Outer fabrication (body) construction	304 grade Stainless Steel
Tank construction	304 & 316 grade Stainless Steel
<b>DISPENSE FONT(S):</b>	
Dispense Font dimensions (W x D x H) mm	185 x 185 x 225 ( <i>standard font</i> )
Tap font clearance ( <i>standard height font</i> ) mm	150 ( <i>tall font option available with clearance of 250mm</i> )
Dispense font construction:	304 grade Stainless Steel & chrome-plated Aluminium
Font interface with UC unit (electrical & water)	1.2 metre, plug-in XLR lead (electrical) and silicone rubber water transfer tube (water)
<b>ELECTRICAL:</b>	
Power rating (kW)	4.5 (or can be configured as 6.75kW)
Voltage supply	230 V (50-60Hz)
Electrical supply	Single-phase, N & E (20A or 30A)
Electrical Installation	Wire to 30amp (6.75kW) or 20amp (4.5kW) single-phase supply via an isolation switch
Fitted cable length (m)	1.7m
<b>PLUMBING:</b>	
Water inlet connection:	3/4" BSP
Food quality, flexible mains water hose	1.6 metre long, (3/4"BSP)
Mains water pressure range	2 – 7 bar (28psi – 100psi)
Overflow/waste connection:	15mm push-fit (right-side of UC unit)
<b>PERFORMANCE:</b>	
Water temperature delivered	90°C (default for stadiums) – adjustable between 80°C & 95°C
Heat up time to working temperature	40 mins (@ 6.75kW) or 63 mins (@ 4.5kW)
Output per hour (@ default temperature setting)	63 Litres (@ 6.75kW) or 44 Litres (@ 4.5kW)
Rapid draw-off	47 Litres
Recovery per minute	1.2 Litres (6.75kW) or 0.7 Litres (@ 4.5kW)
Stand-by power loss (idle mode)	0.12 kW/h
<b>FILTRATION:</b>	
Multi-Filter (taste & odour, sediment & reduces lime-scale)	No ( <i>available as an optional extra if required</i> )
<b>OTHER FEATURES:</b>	
Choice of measured water delivery (with top-up or on-demand setting)	Yes
Tank-baffle plates – unique design aids heat recovery & reduces steam emissions to atmosphere	Yes
Early warning lime-scale diagnostics (3 sensors)	Yes
Dual safety protection	Yes - Over-boil & boil-dry protection
<b>STANDARDS &amp; APPROVALS:</b>	
WRAS approved	Yes
EMC Tested and Certified (EN 55014 & EN 61000)	Yes
Electrical Safety Tested and Certified to BS standard	Yes ( <i>self-certified</i> ) - BS EN 60335-1 & 2
<b>WARRANTY &amp; AFTER-SALES:</b>	
Guarantee	2 Year parts & labour
Spare parts, filters & accessories	Same day despatch (if ordered before 3pm)

Instanta Limited

T: 01704 501114 F: 01704 501115 E: [sales@instanta.com](mailto:sales@instanta.com)



Certificate Numbers: FM01234 & EM01234