

UR90G-SUB ZERO


Sub Zero Cooler / Caviar Cooler

Product Features

- Fully automatic
- Fan assisted cooling
- Vertical LED interior light with switch
- Heated glass door to prevent condensation
- Adjustable shelves
- Digital controller and temperature display

The TEFCOLD UR90G, the perfect table-top refrigerated for displaying caviar and other products you may want to keep subzero temperatures . With an electronic thermostat and thermometer, our ventilated cooling system ensures an even and stable temperature on all shelves. It preserves the quality, taste, and texture of your caviar with the correct temperature range. Our sleek design, complete with internal LED lighting and heated double glazed door (to help prevent condensation build up), ensures a visually impressive presentation of your products.

Measures and Content		
Temperature Range	°C	-8 to +6
Climate Class		4
Gross / Net Weight	kg	39.5 / 35.5
Gross / Net Volume	1	92 / 81
Design and Material		
Door Number & Type		1 heated hinged glass door
Tempered glass		Yes
Door Reversible		No
Shelves Number & Type		3 wire shelves black
Shelf Color		Black
Shelf Dimensions		420 x 300 mm
Max load on Shelves	kg/m²	196
Feet / Legs		4 adjustable feet
Exterior Finish		Black
Interior Finish		Black
Interior Light		LED cold white vertically
Lock		Yes
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		R600a
Refrigerant Charge	g	40
Thermometer		Yes
Power and Consumption		
Energy Class		E
Energy Consumption	kWh/24h	1.51
Annual Energy Consumption	kWh/year	551
Power		13 Amp
Max Ambient		30°C at 55% RH
Input Power	W	280
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	42
Dimensions		
Internal Dimension (WxDxH)	mm	439 x 299 x 632
External Dimension (WxDxH)	mm	515 x 542 x 750
Packed Dimension (WxDxH)	mm	570 x 585 x 805
40ft Container Load	pcs	160





Gross / Net Weight	kg	1
Gross / Net Volume	I	
Door Number & Type		
Shelves Number & Type		
Internal Dimension (WxDxH)	mm	
External Dimension (WxDxH)	mm	x x
Packed Dimension (WxDxH)	mm	хх

Þ	rod	uct	Fea	tu	res
_	ı uu	ull	гса	ш	162

