



UTENSIL WASHER UX-1300C 230-400/50/3N DD

Rack size 1320 mm x 700 mm and door clearance 820 mm. Constant temperature rinsing system.



1303540



WARE WASHING
POT WASHERS

SALES DESCRIPTION

Ideal to wash big sized pots and wares.

- ✓ Powerful and high pressure: specially indicated for restaurants, ice-cream shops, pastries and butcheries.
- ✓ Constructed from stainless steel.
- ✓ Door divided in two parts, perfectly counterbalanced, easy to handle.
- ✓ Double skinned machines: silent working and reduced thermal dispersions.
- ✓ Wash tank without corners to avoid dirt accumulation in angles.
- ✓ Stamped wash dispersers in stainless steel tubes.
- ✓ Easy to remove wash- and rinse dispersers.
- ✓ Safety micro switch at the door and electronic safety device to guarantee washing temperature and time.
- ✓ Advanced LCD control panel with humidity protection. Display of wash and rinse temperatures.
- ✓ Reduced water consumption.

INCLUDES

- ✓ 1 stainless steel basket and insert for 4 trays.
- ✓ Adjustable detergent and rinse aid dosing equipment.

OPTIONAL

- ☐ Stainless basket.
- ☐ Drain pump with level sensor. Proactive tank water renewal.
- ☐ Stainless carrier for trays.

ACCESSORIES

- ☐ Stainless steel baskets
- ☐ Dosing equipments
- ☐ Manual water softeners
- ☐ Carrier for trays
- ☐ Automatic water softeners

SPECIFICATIONS

Basket dimensions: 1320 mm x 700 mm
Stainless steel basket: 1
Equipment: supplementary trays: 1
Useful height: 820 mm
Cycles: 5
Cycle duration: 120 / 180 / 240 / 360 / 480"
Production baskets / hour: 30 / 20 / 15 / 10 / 7
Electrical supply: / 50 Hz /
Electrical connection: 3P+N+G

Loading

- ✓ Pump: 3 Hp / 2 x 2200 W
- ✓ Tank: 9000 W
- ✓ Boiler: 12000 W
- ✓ Total loading: 16400 W
- Feed water temperature: 10°C - 60°C
- Wash temperature: 10°C - 60°C
- Rinse temperature: 65°C - 87°C
- Wash tank capacity: 120 l
- Boiler capacity: 20 l
- Water consumption/cycle: 7.5 l
- Drainage base maximum height: 218 mm
- Drain diameter: 30 mm

External dimensions (W x D x H)

- ✓ Width: 1465 mm
- ✓ Depth (closed): 930 mm
- ✓ Depth (open): 1374 mm
- ✓ Height (closed): 2015 mm
- ✓ Height (open): 2330 mm
- Net weight: 322 kg
- Noise level (1m.): 76 dB(A)
- Crated dimensions
1590 x 1020 x 2000 mm
- Gross weight: 334 kg



SAMMIC, S.L. · Basarte, 1
20720 AZKOITIA (Gipuzkoa) · SPAIN

product sheet
updated 24/06/2026

