

British Manufacturing since 1957



The Professionals Choice

WM3SS

Wall Mounted SureFlow Premium Water Boiler



FULL SPECIFICATION



WM3SS Wall Mounted SureFlow Premium Auto Fill Water Boiler

Туре	Premium Wall Mount – Wall mount Water Boiler
Country of Design & Manufacture	UK
CAPACITY, WEIGHTS & DIMENSIONS:	•
Capacity (Litres)	3
Unit dimensions (W x D x H) mm	314 x 215 x 414
Packed dimensions (W x D x H) mm	590 x 440 x 700
Tap protrusion mm	90mm
Product weight - empty (kg)	9.4
Product weight – full (kg)	14.5
Packed weight (kg)	13.4
CONSTRUCTION:	
Outer fabrication (body) construction	304 grade stainless steel
Tank construction	304 & 316 grade stainless steel
Tank wall thickness	0.9mm
ELECTRICAL:	0.011111
Power rating (kW)	3
Voltage supply	230 V (50-60Hz)
Electrical supply	Single-phase, N & E (min break rating of 13amp required)
Electrical Connection	Wire into double-pole fused spare (minimum cable size:
Elocation Control Control	1.5mm²). Use of an ELCB is recommended
PLUMBING:	1.6mm). Ode of all LEOD is recommended
Water inlet connection:	3/4" BSP or 15mm push-fit
Mains water pressure range	2 – 7 bar (28psi – 100psi)
Overflow/waste connection:	15mm push-fit (extend if required: pipework to have a
O VOI IION/ Made O O III O O O O II	continuous fall (no longer than 500mm), no more than 3
	right-angle bends.
PERFORMANCE:	
Water temperature delivered	96°C (default) – can be adjusted if required
Heat up time to working temperature	11 mins (full tank capacity)
Output per hour (@ default temperature setting)	28 Litres (higher output/hour if set @ lower temperature)
Rapid draw-off	3 Litres
Recovery per minute	0.5 Litres
Stand-by power loss (idle mode)	0.1 kW/h
FILTRATION:	V.1 (VV)
Multi-Filter (taste & odour, sediment & reduces lime-scale)	No (available as an optional extra if required)
OTHER FEATURES:	(available de all optional oxità il requirea)
7 day programmable timer	Yes
Energy-saving ECO mode	No
Tank-baffle plates – unique design aids heat recovery &	Yes
reduces steam emissions to atmosphere	100
Early warning lime-scale diagnostics (via LCD display)	Yes
Dual safety protection	Yes - Over-boil & boil-dry protection
STANDARDS & APPROVALS:	. 22 2.0. 20. 3. 20. 4.) p. 0.0000
WRAS approved	Yes
EMC Tested and Certified (EN 55014 & EN 61000)	Yes
Electrical Safety Tested and Certified to BS standard	Yes
EN 60335-1 & 2	. • •
WARRANTY & AFTER-SALES:	
Guarantee	2 Year parts & labour
Spare parts, filters & accessories	Same day despatch (if ordered before 3pm)
- []	

Instanta Limited T: 01704 501114 F: 01704 501115

E: sales@instanta.com





Certificate Numbers: FM01234 & EM01234