

Features and Benefits

- Fully automatic
- Fan assisted cooling
- Adjustable feet
- Digital controller and temperature display
- Replaceable door gasket
- Temperature probe
- 4 Pre-settable programs
- Internal rounded corners for easy cleaning
- Shelf racks removable for easy cleaning
- Simple access to fans for cleaning
- Accepts 1/1 Gastronorm and 60x40 Euronorm pans (not supplied)
- Y2-3 accepts Gastronorm only
- Y2-3 (Chill +70°C to +3°C) 10kg in 90 mins
- Y2-3 (Freeze +70°C to -18°C) 6kg in 240 mins
- Y2-5 (Chill +70°C to +3°C) 20kg in 90 mins
- Y2-5 (Freeze +70°C to -18°C) 14kg in 240 mins
- Y2-7 (Chill +70°C to +3°C) 30kg in 90 mins
- Y2-7 (Freeze +70°C to -18°C) 20kg in 240 mins
- Door not reversible

Technical Specifications

Refrigerant	R404a
Type of Defrost	Off Cycle
Exterior Finish	Stainless Steel
Interior Finish	Stainless Steel
Power Required	13 Amp
Max Ambient	30°C at 55% RH
Climate Class	4



Touchscreen controller



Y2-5



Y2-3



Y2-7

Model	Description	Dimensions (mm)			Kg	Gross Int. Volume	Price	Next Day	
		H	W	D					
Y2-3	3 Tray	Ext.	500	670	715	55	47ltr (1.66 cu.ft)	£2,238	✓
		Int.	235	340	590				
Y2-5	5 Tray	Ext.	850	810	830	100	108 (3.81 cu.ft)	£2,784	✓
		Int.	345	670	465				
Y2-7	7 Tray	Ext.	1070	810	830	130	148ltr (5.23 cu.ft)	£3,813	✗
		Int.	475	670	465				